

DELO-XPRESS 921 (NK)

DELO

DELO-XPRESS 923 (NK)



Pressure tank for DELO FLEXCAP

The pneumatic pressure tanks DELO-XPRESS 921 & 923 are used for bubble-free dispensing via the hermetically sealed in-house developed DELO FLEXCAP. They can optionally be operated with a level sensor.

Technical data

DELO-XPRESS 921 (NK)

DELO-XPRESS 923 (NK)

	DELO-XPRESS 921 (NK)	DELO-XPRESS 923 (NK)
Dimensions	With NK: 125 mm (H), outer-Ø: 51 mm Without NK: 68,5 mm (H), outer-Ø: 51 mm	With NK: 125 mm (H), outer-Ø: 51 mm Without NK: 68,5 mm (H), outer-Ø: 51 mm
Fill volume	DELO FLEXCAP container, 10 ml	DELO FLEXCAP container, 30 ml
Volume	0.025 l	0.074 l
Level sensor (NK)	Proximity switch (reed contact)	
Weight	With NK: 143 g Without NK: 58 g	With NK: 197 g Without NK: 134 g
Operating temperature	+5 °C to +45 °C	
Operating pressure	Min. 2 bar	Max. 6 bar
Operating medium	Compressed air (dry, dust-free ambient air)	
Product compatibility	DELO FLEXCAP	



Contact us: equipment-experts@DELO.de