

DELOTHEN® EP

Base

- solvent mixture
- free of CFC/FC-containing ingredients and aromas

Use

- preferably for the cleaning of equipment or systems contaminated with epoxy resin components
- cleaning must be carried out before complete curing of the epoxy resins
- cleans metal, glass, ceramic, rubber and plastic
- the behavior of thermoplastics towards DELOTHEN EP cleaner is to be tested in a short test where necessary
- oil- and grease-containing contaminations as well as uncured residues of epoxy resin components can be removed well
- very short evaporation time
- store the container closed
- evaporates without leaving any residues

Processing

- rinse the equipment with equipment cleaner EP or deposit contaminated equipment elements and tools in solvent
- wipe off with a clean, absorbent, lint-free cloth
- repeat this procedure until complete cleaning
- after complete evaporation of residual cleaner on the surfaces or possibly formed condensation water, the equipment or tool can be used again
- take precautionary measures against static discharges

Technical data

Color

colorless clear

Evaporation time [min]

at room temperature (approx. 23 °C)

approx. 2

Storage life at room temperature (max. 25 °C)

in unopened original container

12 months

Instructions and advice

General

The data and information provided are based on tests performed under laboratory conditions. Reliable information about the behavior of the product under practical conditions and its suitability for a specific purpose cannot be concluded from this. It is the customer's responsibility to test the suitability of the product for the intended purpose by considering all specific requirements. Type and physical and chemical properties of the materials to be processed with the product, as well as all actual influences occurring during transport, storage, processing and use, may cause deviations in the behavior of the product compared to its behavior under laboratory conditions. The data and information provided are therefore no guarantee for specific product properties or the suitability of the product for the intended purpose.

Nothing contained herein shall be construed to indicate the non-existence of any relevant patents or to constitute a permission, encouragement or recommendation to practice any development covered by any patents, without permission of the owner of this patent.

All products provided by DELO are subject to DELOs' General Terms of Business. Verbal side agreements are not permitted. This document is subject to change.

Occupational health and safety

see material safety data sheet

Specification

The properties in italics are part of the specification. Ranges with clear limits are defined for them and others, where applicable. In the course of the QA test, each batch is tested for these properties and the maintenance of the limits is ensured. The measuring methods used can deviate from those specified in the data sheet. Details can be found in the QA test report.