

### **DELOTHEN® NK1**

cleaner

#### **Base**

- solvent mixture
- free of CFC/FC-containing ingredients and aromas

#### **Use**

- for the cleaning of components and the removal of grease from surfaces, especially for the preparation of bonding surfaces
- cleans metal, glass, ceramic, rubber and plastic
- the behavior of thermoplastics towards DELOTHEN NK1 is to be tested in a short test where necessary
- oil- and grease-containing contaminations can be removed well
- very short evaporation time
- evaporates without leaving any residues

#### **Processing**

- the cleaner is directly sprayed on the surfaces to be cleaned from a distance of 20 - 30 cm
- a suitable precleaning method is recommendable in case of strong contamination
- high amounts of solvent on the surface are to be removed with a clean, absorbent and lint-free cloth; in doing so, the cleaning effect is supported at the same time
- evaporation times of 2 - 3 min can be reached
- it is recommendable to determine the actual evaporation time under original conditions
- after complete evaporation of residual cleaner on the surfaces or possibly formed condensation water, processing of the components, e. g. adhesive application, can continue
- store the container closed
- take precautionary measures against static discharges
- CONSIDER FLASH POINT!

#### **Technical data**

*Color*

colorless clear

Evaporation time [min]

2 - 3

at room temperature (approx. 23 °C)

Storage life at room temperature (max. 25 °C)

12 months

in unopened original container

## **Instructions and advice**

### **General**

The data and information provided are based on tests performed under laboratory conditions. Reliable information about the behavior of the product under practical conditions and its suitability for a specific purpose cannot be concluded from this. It is the customer's responsibility to test the suitability of the product for the intended purpose by considering all specific requirements. Type and physical and chemical properties of the materials to be processed with the product, as well as all actual influences occurring during transport, storage, processing and use, may cause deviations in the behavior of the product compared to its behavior under laboratory conditions. The data and information provided are therefore no guarantee for specific product properties or the suitability of the product for the intended purpose.

Nothing contained herein shall be construed to indicate the non-existence of any relevant patents or to constitute a permission, encouragement or recommendation to practice any development covered by any patents, without permission of the owner of this patent.

All products provided by DELO are subject to DELOs' General Terms of Business. Verbal side agreements are not permitted. This document is subject to change.

### **Occupational health and safety**

see material safety data sheet

### **Specification**

The properties in italics are part of the specification. Ranges with clear limits are defined for them and others, where applicable. In the course of the QA test, each batch is tested for these properties and the maintenance of the limits is ensured. The measuring methods used can deviate from those specified in the data sheet. Details can be found in the QA test report.